

**KANSAS DEPARTMENT OF TRANSPORTATION
SPECIAL PROVISION TO THE
STANDARD SPECIFICATIONS, EDITION 2007**

Add a new section to DIVISION 1200:

WARM MIX ASPHALT ADDITIVES

1.0 DESCRIPTION

This specification covers Warm Mix Asphalt (WMA) additives and processes.

2.0 REQUIREMENTS

Provide prequalified WMA additives or processes.

3.0 TEST METHODS

WMA additives and processes will be tested and evaluated by the Texas Department of Transportation following the procedures outlined in **subsection 4.0**.

4.0 PREQUALIFICATION

Obtain prequalification procedures by writing to the Texas Department of Transportation, Director of Construction and Maintenance, 125 East 11th Street, Austin, TX 78701-2483. A list of prequalified additives and processes based on the prequalification process for the Texas Department of Transportation and field performance within Kansas will be maintained by the KDOT Bureau of Materials and Research. The KDOT prequalified list establishes the acceptable additives and processes to be incorporated into KDOT projects. Products will remain on the KDOT list provided field performance is satisfactory. Products may be removed from the KDOT list if the manufacturer requests the removal of their own product.

5.0 BASIS OF ACCEPTANCE

a. WMA Foaming Processes.

- (1) Prequalification as required by **subsection 4.0**.
- (2) Field observation of WMA production.

b. WMA additives.

- (1) Prequalification as required by **subsection 4.0**.
- (2) Receipt and approval of a Type C certification as specified in **DIVISION 2600**.
- (3) Field observation of WMA production.

07-23-10 M&R (GS)
Oct-10 Letting