### 1604 - HELICAL REINFORCEMENT

# **SECTION 1604**

### HELICAL REINFORCEMENT

### 1604.1 DESCRIPTION

This specification covers steel wire and steel bars intended for use in helical reinforced members.

# **1604.2 REQUIREMENTS**

Provide materials that comply with AASHTO M 32 for plain, uncoated wire, or AASHTO M 31 for carbon steel bars.

## 1604.3 TEST METHODS

Test methods as cited in the AASHTO references.

## **1604.4 PREQUALIFICATION**

Manufacturers desiring to provide material under this specification must be prequalified under the provisions of:

•	Steel bars	SECTION 1601
•	Uncoated wire	SECTION 1603
•	Epoxy coated reinforcement	SECTION 1602

# 1604.5 BASIS OF ACCEPTANCE

Prequalification as required by subsection 1604.4.

Submit for approval a Type A certification (certified mill test report), as specified in **DIVISION 2600**, that governs the analysis of all bar or wire steel heats delivered to the project.

Receipt and approval by the Engineer of a copy of the shipping orders or invoice showing the project number, heat or lot number, steel size and quantity in the shipment.

Tag each bundle of helical reinforcement sent to the project with a plastic or metal tag which lists the plant name and the heat or lot number, or other identification tying the material to the certifications and invoices as stated above in this subsection.